

Cassese CS 79 FOOT OPERATED UNDERPINNER  
NEW VERSION TOP PRESSER (item # Z6232)



This new version top presser comes now with your CS 79 as a standard feature. Its height can be adjusted with the pin so that the machine can work up to 78 mm (3"1/8) tall mouldings. Pay attention to keep always maximum 30mm (1"1/4) distance between the top presser and the mouldings and to keep the rubber triangle parallel to the 90° angle assembly (backfences B1 & B2, Fig.1, p. 1)



The moulding height capacity of the new triangle top presser support for its 4 positions :

- 1) 37 mm (1"1/2)
- 2) 53 mm (2"1/8)
- 3) 68 mm (2"3/4)
- 4) 78 mm (3"1/8)

**OPTIONAL ACCESSORY (Cassese item # Z.6233)**

A similar adjustable support for the round rubber top pressers is now available with 3 positions for its height.

As the round rubbers are available in two lengths (30mm & 45mm) and in two hardness finishes (orange for softwoods & green for very hardwoods), the maximum height of moulding that this optional round rubber support can work in its three positions are :

Position hole #	With short round rubber	With long round rubber
1	37 mm (1"1/2)	22 mm (7/8")
2	53 mm (2"1/8)	37 mm (1"1/2)
3	68 mm (2"3/4)	53 mm (2"1/8)

**IMPORTANT :**

**In any position of the top presser, to insert wedges fully in, the distance between the moulding and the down end of the top presser shall not exceed 30 mm (1"1/4). If so, change the position of the top presser and bring it closer to mouldings.**