



T2xxx

Manual Pneumatic Double Mitre Saw


Our Double Mitre Saws are designed to precisely cut mitres for picture frames, windows, doors, and furniture components.

It is a heavy duty saw built to last many years in a high production environment.


The machine has a unique pneumatic control system which totally supports the weight of the cutting assembly allowing a very smooth down-stroke, precise cuts, and a quick return.

These saws utilize vertical drop technology that was developed over many years in production, which reduces scrap, having a knockout as small as 1.6mm (1/16").

During the cutting process, the moulding cannot move as it is held firmly to the workbench by four pneumatic clamps ensuring high quality cuts every time.



Details of the cutting group



Cutting diagram

THE INFORMATION AND DATA PROVIDED MAY BE SUBJECT TO MODIFICATION WITHOUT PRIOR NOTICE

A-Plus Automation USA Inc. Phone 1-800-539-2750
 31874 Northwestern Hwy. Fax 248-851-8777
 Farmington Hills, MI 48334 Email info@aplusautomationusa.com
 Web www.aplusautomationusa.com





Manual Pneumatic Double Mitre Saw

Data Sheet

	VOLUME	WEIGHT	MOULDING SIZE	SAW MOTOR	PRESSURE	CONSUMPTION	PRODUCTIVITY	BLADES	ELECTRIC CTRL BOX
T2300	750x800x1550mm	≈500 Kg	A max 80mm B max 60mm	2x1,5Kw (400V-3PH)	4-8 BAR	8 NL at 5 Bar 0.28 cf ³ at 73 PSI	12	A = 30mm B = 300mm 3000 rpm	3.0Kw 400V
T2350			A max 80mm B max 80mm					A = 30mm B = 350mm 3000 rpm	
T2400			A max 80mm B max 100mm					A = 30mm B = 400mm 3000 rpm	
T2450			A max 80mm B max 120mm					A = 30mm B = 450mm 3000 rpm	

Standard Accessories

- Adjustable down stroke speed
- Fast readout measurement gauge and metric ruler to read the Internal or external dimension of the frame. (inch gauge optional)
- Dual measurement stops
- External scrap chute
- Infeed and outfeed tables
- Quick change blades
- Emergency shut off button
- Blade door with safety switch
- Adjustable height blade guard
- Two-hand control via thumbbuttons
- Two 1.5 kw (2HP) Braking motors
- Two 80mm (3") dust collector ports

Optional Accessories



Multiple vertical clamping system



Horizontal clamps

AL Aluminum cuts



Mist spray cooling system



Refrigerating without lubrication



Right Extension with gauge
Left Extension without gauge



Special blades for wood or for aluminum

